

MOTORDYNE ART PIPE INSTALLATION

On the driver side floor panel heat shield there is a M6 stud that protrudes down about 1". This stud will create an interference fit. Trim the stud flush down to the panel to allow for ART pipe clearance. Install all the bolts for the ART pipes only finger tight, then adjust rotation/alignments as needed, then tighten all the bolts working from front to back starting at the inlet to the brace to the outlet.

Tighten bolts to 60 ft/lbs torque. Checking and retightening the bolts is recommended after ~100 miles of driving to insure a good permanent seal. The vibration dampening bracket on the side-branch resonator must be connected to the catalytic converter brace. Failure to do so may cause the pipe to eventually crack and voids warranty.

If you have any questions during your installation feel free to contact us at: (661) 993-5111

Thank you,
Motordyne Engineering



Motordyne Warranty Terms and Conditions

Many parts are for off-road use only. As with any racing activity, there are risks at performance modifications. All installions are at the customers own risk. Motordyne Engineering holds no responsibility either implied or otherwise for mechanical, electrical or other failure when using after market performance products. Some items listed are illegal in many states and only for racing vehicles which may never be used on a public highway.

Warranty Policy of MOTORDYNE Inc. warrants to the original retail purchaser that the MOTORDYNE product will be free from defects in material and workmanship for one year from the date of original purchase except for: Full stainless steel exhaust and piping, which are warranted for two years from original purchase. This warranty does not apply where the product is purchased from an unauthorized Motordyne dealer.

The product has been abused, salted, misused, damaged or improperly maintained, repairs have been made or attempted by others, because of normal tarnish, wear or tear, alterations have been attempted or made to the product, the product is a consumable, the product has been in an accident.

This non-transferable warranty is limited to repair or replacement, without charge, of the product/part found to be defective or, at MOTORDYNES option, refund of the purchase price and does not extend to claims for other loss or damage arising from the defect. Warranty is applicable only with a receipt from authorized Motordyne dealers. If a part does not fit or work properly, is blemished or is the wrong part, do not start the engine and uninstall the part immediately. Parts must be returned for inspection and approval before replacements can be sent. If a part or component from a Motordyne system/kit is found to be defective, this warranty shall apply only to the defective part or component and shall not require MOTORDYNE to repair, replace or refund the complete MOTORYDNE system/kit. In no event shall MOTORDYNE liability under this warranty exceed the purchase price of the MOTORDYNE product.

This warranty does not include the cost of removal, shipping or re installing of the product. No person or representative is authorized to extend any warranties on behalf of MOTORDYNE (other than expressed herein) or assume for MOTORDYNE any liability (other than expressed herein) in connection with the sale of any MOTORDYNE product.

MOTORDYNE DISCLAIMS ANY AND ALL LIABILITY FOR ANY IMPLIED WARRANTY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A SPECIFIC PURPOSE. UNDER NO CIRCUMSTANCES SHALL MOTORDYNE BE LIABLE FOR ANY INCIDENTAL, INDIRECT, SPECIFIC OR CONSEQUENTIAL DAMAGES ARISING FROM PURCHASERS USE OF THE PRODUCT. Some states do not allow one or more of the above specified exclusions or limitations. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Motordyne is not responsible for loss or damage caused during shipment. This is the responsibility of the carrier. All orders are shipped fully insured to protect against theft, loss, rifling and damage. Damaged parts must be reported to shipping carrier immediately.

All returns must be approved by MOTORDYNE with an RMA#.

All returns must be in the original box.

No returns on used or damage products.

All Non-defective returns are subject to a 20% restocking fee.